

DIN6527 SOLID CARBIDE END MILLS

- Manufacturing process: fully ground
- Spiral angle: 30°, 45°, 60°
- Flutes: 2 flutes Type: ball nose
- Material: tungsten carbide
- Finish: bright, TiN, TiALN
- Diameter: 3.0-20.0mm



6527K

D	d	FL	OAL
3.0	6.0	4	50
3.5	6.0	4	50
4.0	6.0	5	54
4.5	6.0	5	54
5.0	6.0	6	54
6.0	6.0	7	54
7.0	8.0	8	58
8.0	8.0	9	58
9.0	10.0	10	66
10.0	10.0	11	66
12.0	12.0	12	73
14.0	14.0	14	75
16.0	16.0	16	82
18.0	18.0	18	84
20.0	20.0	20	92

6527L

D	d	FL	OAL
3.0	6.0	7	57
3.5	6.0	7	57
4.0	6.0	8	57
4.5	6.0	8	57
5.0	6.0	10	57
6.0	6.0	10	57
7.0	8.0	13	63
8.0	8.0	16	63
9.0	10.0	16	72
10.0	10.0	19	72
12.0	12.0	22	83
14.0	14.0	22	83
16.0	16.0	26	92
18.0	18.0	26	92
20.0	20.0	32	104

DIN6527 SOLID CARBIDE END MILLS

- Manufacturing process: fully ground
- Spiral angle: 30°, 45°, 60°
- Flutes: 4 flutes Type: ball nose
- Material: tungsten carbide
- Finish: bright, TiN, TiALN
- Diameter: 3.0-20.0mm



6527K

D	d	FL	OAL
3.0	6.0	4	50
3.5	6.0	4	50
4.0	6.0	5	54
4.5	6.0	5	54
5.0	6.0	6	54
6.0	6.0	7	54
7.0	8.0	8	58
8.0	8.0	9	58
9.0	10.0	10	66
10.0	10.0	11	66
12.0	12.0	12	73
14.0	14.0	14	75
16.0	16.0	16	82
18.0	18.0	18	84
20.0	20.0	20	92

6527L

D	d	FL	OAL
3.0	6.0	7	57
3.5	6.0	7	57
4.0	6.0	8	57
4.5	6.0	8	57
5.0	6.0	10	57
6.0	6.0	10	57
7.0	8.0	13	63
8.0	8.0	16	63
9.0	10.0	16	72
10.0	10.0	19	72
12.0	12.0	22	83
14.0	14.0	22	83
16.0	16.0	26	92
18.0	18.0	26	92
20.0	20.0	32	104